

FOLD HERE AND
ALIGN TEMPLATE
ON HIGH EDGE OF
DOOR BEVEL.

FOLD HERE AND
ALIGN TEMPLATE
ON HIGH EDGE OF
DOOR BEVEL.

3/8" DIA.

3/8" DIA.

13/16"

13/16"

1" THRU HOLE
FOR FIRE-RATED DOORS

7/8" DIA. WIRE THRU HOLE
FOR NON FIRE-RATED
DOORS ONLY

**FOR INSTALLING
ALL TRILOGY
CYLINDRICAL
LOCK MODELS**

1/8" MIN. DEPTH NOTCH
BOTH SIDES OF DOOR

3/8" DIA.
(2 PLACES)

5 13/32"

3 9/16"

2 1/8" DIA.

2 5/8"

BORE 1" DIA.
LATCH HOLE

5/32" DEEP

2 9/16"

5/32"

1 3/4" (45mm)

1 3/4" (45mm)

1 3/8" (35mm)

1 3/8" (35mm)

2 3/4"

2 15/32"

2 3/4"



ALARM LOCK

345 Bayview Avenue
Amityville, New York 11701
For Sales and Repairs 1-800-ALA-LOCK
For Technical Service 1-800-645-9440
Publicly traded on NASDAQ Symbol: NSSC
© ALARM LOCK 2009